

SUNSHADE SPECIFICATIONS

| PART # | DESCRIPTION | PERFORATED OPEN AREA | MAX WIND LOAD RATING (LBS/SQFT) | MAX SNOW LOAD RATING (LBS/SQFT) | BOLT SHEAR LOAD (LBS/EA BOLT) | BOLT TENSION LOAD (LBS/EA BOLT) |
|----------|-------------------------------------------------------------------------|----------------------|---------------------------------|---------------------------------|-------------------------------|---------------------------------|
| SDF31079 | CORVO (1/8" 5052-H32 x 24" x 48") WITH INTERGRADED MOUNTING BRACKET | 30% | 36 ^{1,4} | 40 ^{1,5} | 42 ^{2,6} | 266 ^{2,6} |
| | | 40% | 41 ^{1,4} | 40 ^{1,5} | 42 ^{2,6} | 266 ^{2,6} |
| SDF31081 | PIANA (1/8" 5052-H32 x 24" x 48") WITH TWO (SD033369) MOUNTING BRACKETS | 30% | 57 ^{1,4} | 40 ^{1,5} | 70 ^{3,6} | 704 ^{3,6} |
| | | 40% | 66 ^{1,4} | 40 ^{1,5} | 70 ^{3,6} | 704 ^{3,6} |

NOTES:

1. INCLUDES 2.5 X SAFETY FACTOR.
2. SHADE IS MOUNTED WITH 8 BOLTS (4 BOLTS EACH SIDE).
3. SHADE IS MOUNTED WITH 6 BOLTS (3 BOLTS EACH SIDE).
4. WIND LOAD IS REDUCED/INCREASED BY OPEN AREA.
5. OPEN AREA DOES NOT EFFECT SNOW LOAD.
6. LOAD BASED ON 40 LBS/SQFT.

Note: For Custom sizes please contact us at 800-225-7373 to discuss